

60007 Rugged SDI Video Monitor

4 input - various formats with NVIS display option

Features

- 17.3" Full HD Display
- Anti Glare Glass or PCAP touch screen options
- Day/Night operation with NVIS white Class B.
- 4 SDI inputs as standard (any formats)
- Option of a mix of SDI & HDMI inputs
- Other input formats including CVBS as options
- Built in multi-viewer with 6 layouts as standard.
- SDI outputs of screen display 1080P 60 (others on request)
- Surge protected and filtered PSU compliant to DO160
- 28vdc nom (16-40Vdc) with 12v option
- Remote Record Button for DVRs
- 100mm VESA mount standard (optional rack kit available)
- Low power consumption



The 60007 HD display has been designed to meet a wide range of applications where various standards of SDI video, HDMI and even composite video are required to be displayed in a single monitor.

The output of the monitor is SDI format and is the mimic of what is displayed on the screen.

The inputs are 4 SDI video (any format) as standard but the monitor can accept permutations such as 2 SDI and 2 HDMI inputs or even 3 SDI plus 1 CVBS input depending on the configuration requested at time of order.

Standard options are Anti Glare Glass or PCAP touch screen panels, and a resistive touch screen option is also available.

The display layout is selected by a rotary switch, with any 4 inputs full screen, a quad display and inputs 1 & 2 displayed side by side. Other layouts are available - kindly contact the factory.

A remote record button with tell-back is included on the front panel to interface to the Britannia 60005 DVR.

The monitor power circuit complies with DO 160 requirements and is surge resistant. The standard unit operates from 28v nominal (16-40vdc).

A 100mm VESA mount is standard and a rack mount kit is available.

Britannia welcomes requests for custom options and the design enables us to incorporate personality modules to meet customer requirements.



Specifications

Display	17.3" LCD, 1920x1080P/60 as standard Full membrane control and OSD with multi-language: English, French, Spanish, German Hard ON/OFF switch NVIS white class B compliant
Special functions	Day/Night Mode select (max brightness 20 nits night/800nits day) Backlight Kill Rotary switch selection of display view format Illuminated record button with tell back for integration to the B2KH 60007 DVR (or other external DVR on request.)
Signal	
Video inputs	SDI BNC (x4) HMDI option Composite Video option Display port option
Video out	SDI BNC (x2)
Analog audio I/O	Line, LEMO 2B
Display Formats	6 preset display views. Each input full screen, quad display and inputs 1 & 2 side by side centralised. Other patterns available -contact factory
SDI input format	3 G-SDI, SMPTE 259/292/424 1080p - 23.98, 24, 25, 29.97, 30, 50, 59.94, 60 1080psf - 23.98, 24, 25, 29.97, 30 1080i - 50, 59.94, 60 720p - 23.98, 24, 25, 29.97, 30, 50, 59.84, 60 NTSC - 480i PAL - 575i
Power	
Input	28v dc nominal (16 ~ 40v), 50w (12vdc factory option available)
Environmental	
Operational	0°C to +60° C (low temperature option available)
Relative humidity	20 ~90% RH(non-condensing)
Shock and Vibration	Designed to meet RTCO 160G
Physical	
Size	409 mm(w) x 290mm(h) x 75mm(d)
Weight	6.2Kg 3mm toughened glass anti glare 5.2Kg with PCAP touch screen 4.5Kg no AG glass or touch screen

Ordering Information

60007-01	Monitor with 4 x SDI inputs
60007-02	Monitor with 3 x SDI + 1 x HMDI inputs
60007-03	Monitor with 2 x SDI + 2 x HMDI inputs

Options

/PCAP	(fitted with PCAP touch screen)
/LW	(no AG glass or PCAP)
/RM	(supplied with rack mount kit)

Accessories

60007-11 Connector kit (cable connectors for Video (BNC) Power (LEMO), Remote (LEMO), Audio (LEMO))

Custom

Contact factory for custom colours and various input or display view formats. Our designs are based on being able to provide exactly what is required for your application. Other screen sizes available.